

Kiosk



VariKIOSK 217W

17.3" Desktop Self-Service Kiosk

Poindus
COMPAL GROUP

Features

- Fully integrated AIO desktop self-service kiosk.
- Support Intel® 12th Generation Core i3 & i5 CPU.
- Intel® TPM protect system & data with software-based security hardening.
- True flat 17.3" 9:16 LCD, 300 nits brightness with front bezel IP54 dust & spill water resistant.
- RAID 0/1 function with dual SSD/HDD support (optional).
- Durable die-cast aluminum chassis; built to last.
- Redefines serviceability from design with easy access & quick swap modular design for.
- Rotatable Display (Horizontal or Vertical) (optional).
- Design flexibility of front bay to accommodate various printers and scanners.
- Multiple Rear Display Options (optional).
- Integrated AI Camera (optional).



Specification

Model Name		VariKIOSK 217
Motherboard code		PE26
Main Board	Processor	Intel® Alder Lake-P Platform Core i5 up to 4.4 GHz Core i3 up to 4.4 GHz
	Chipset	Iris® Xe Graphics eligible
	System Memory	1 x SO-DIMM DDR5 slot, 8GB RAM as standard. Max. memory support up to 32GB
	TPM	Intel® TPM 2.0
Display & Touch	LCD Size	17.3" 16:9 TFT LCD(LED backlight)
	Brightness	300nits
	Resolution	1920 x 1080
	Touch Technology	True-Flat PCAP multi-touch screen
Storage	Orientation	Rotatable Screen (Optional)
	SSD	2.5" 256G (Default) as standard
	RAID Function	*Project Based
	DC Input	1 x Mini Din 4P (DC 19V only)
Motherboard I/O & Expansion	Cash Drawer	1 x RJ-11 (Support DC +12V or +24V (default)) port supports 2 cash drawers
	LAN port	1 x Gigabit Ethernet by RJ-45
	USB port	3 x USB 2.0, 3 x USB 3.1
	COM port	3x COM (COM1/2: RJ48 support DC+0/5/12v by BIOS setting, default setting is 0v. COM3: DB-9)
	VGA port	1 x DB-15 VGA port Power enable by BIOS setting (default disable)
	Bus Expansion	1 x M.2 M Key for SSD 1 x M.2 E Key
	Power Switch	1 x power on / off switch button
	Speaker	HD Audio, 2W Speaker x 2
	Type-C	1 x Type C (PD + DP)
	Powered USB port	2 x DC+12v and 1 x DC+24v (Project Based)
OS Support	Win 11 IoT GAC	
Power Adapter	DC+19V, 90watt	
Peripherals	Handheld scanner - Newland NLS-HR3280	
	2D Scanner - Datalogic Magellan1500i	
	Omnidirectional scanner - Datalogic Magellan M3450	
	Printer - Epson TM-M30 III	
	10.1" 16:10 @ 1280 x 800 2nd screen PinPad Bracket for Verifone VX820	
Compliance	Certifications	CE, FCC, LVD, RoHS
	Protection	IP54 on front panel
Material	Main Unit: Die-Cast Aluminum ; I/O Cover:Plastic	
Color	White	
Dimension(Wx H x D)	Vertical mode	
	Main Unit: 270 x 608.7 x 234.6 mm	
	Main Unit + Peripherals: 377.6 x 608.7 x 234.6 mm	
	Horizontal mode	
Weight	Main Unit: 437 x 533.7 x 216.9 mm	
	Main Unit + Peripherals: 489.6 x 533.7 x 237.1 mm	
	12Kg	
Environmental	Operating Condition	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
	Storage Condition	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing

Contact

5F, No.59, Ln. 77, Xing-Ai Rd., Neihu Dist., Taipei City 114, Taiwan. R.O.C

+886 2 7721 4688 +886 2 7721 2289 sales@poindus.com